



TENDER DOCUMENTS

Procurement & Installation of Gym Equipment

IC / SCM / 2025/26 /

TD- 32

ISLAMABAD CLUB

TENDER NOTICE
Islamabad Club (IC)

IC / SCM /

2025/26 / Procurement & Installation of Gym Equipments TD- 32

1. Sealed bids are invited from Government / FBR Registered Firms for the Procurement & Installation of Gym Equipments for IC on **FOR Basis**.
2. Bidding documents containing detailed terms & condition for submission of bids, method of procurement **(Single Stage Two Envelopes)**, eligibility etc. are available for registered bidders on EPADS. Quotations shall be submitted as per requirement of the tender documents.
3. **Tender Documents** can be downloaded from **IC/EPADS** websites and Bids will be submitted as per requirements mentioned in the tender documents. Bid will be submitted through EPADS and bidders will submit their original CDR of **3%** of quoted amount in the favor of" Islamabad Club-----".
4. Submit **Rs 5000/-** as Tender fee in favor of IC (Faysal Bank, Tendering and Contracts, A/C #) attach bank receipt with technical offer. Offers will not be entertained without payment of processing fee.
5. Details for Submission & Opening of bids for tender are as under:-

Ser	Description	Bank Account Details	Tender Fee	<u>Tender Submission</u>	<u>Tender Opening</u>
a.	IC / SCM / 2025/26 / TD- 32	Faysal Bank, Tendering and Contracts, A/C # PK81FAYS0001132031116145	5,000	15:00 Hrs Date 26/12/2025	15:30 Hrs Date 26/12/2025

Note: -

Tender fee in shape of Deposit Slip/Online Submission will be acceptable.
Offer will not be entertained without payment of tender fee.

Supply Chain Management Office (Purchase Office)
(ISLAMABAD CLUB)

Add: asad.ijaz@Islamabadclub.org.pk

Phone: 051-9046000, Ext: 173,176

Compliance – Check List

Offer must be quoted and arranged in accordance with below mentioned sequence.

Non- compliance & non-provision of following documents may lead to disqualification.

Sr.	Required Particulars	Documents Attached	
		Yes / No	Page #
1.	Tender Fee Original Receipt (Rs 5,000/-)		
2.	NTN & GST Registration , Must be ATL		
3.	All Annexures & Special Conditions Compliance Note: All annexures must be as per given format.		
4.	Original bid security 3% of quoted amount		
5.	Complete Tender Document duly signed and stamped each page		
6.	Non-Blacklisting Certificate (Judicial Paper)		
7.	Firm's Complete details (address, contacts & email)		
8.	Must provide OEM Authorization Certificate		

ISLAMABAD CLUB

Tender Documents

1. ISLAMABAD CLUB desires to procure item(s) / Store(s) on FOR Basis as per **Annexure-A**. Interested bidders are requested to upload their bids on EPADS & also submit a hard copy of the same documents in manual at ISLAMABAD CLUB Purchase Office under **"Single Stage Two Envelop"**, procedure latest by or before due date mentioned in the advertisement.
2. **Conditions Governing Contracts.** The contract made as result of this tender document will be in accordance with the draft contract published on ISLAMABAD CLUB website and other special conditions (Mentioned in this document) that may be added to given contract for the Procurement of Gym Equipment.
3. **Participating of Tender.** The offer is to be submitted as under: -
 - a. All Annexure duly filled in (supported with relevant details).
4. **Validity of Offer.** The validity period of quotations must be indicated and should be **120 days** from the date of opening of financial offer.
5. **Withdrawal of offer** If the firm withdraws its offer within validity period the competent authority may place such firm under embargo for a period, which may be extended up to one year. Moreover, the bid security of the firm will be confiscated.
6. **Documents.** Following information / copy of documents must be provided / attached with offer: -
 - a. NTN/GST number be mentioned on the offer and copy of registration certificate issued by sales tax department, attached.
 - b. All the Annexes and special conditions must be signed and stamped. Attach only relevant documents.
 - c. Complete all Annexes as per given format. Do not use your format or letter head.

Offer may be rejected if given format is not followed.
 - d. Must be registered on Active Tax Payer List of FBR
 - e. **Product technical data sheets and detailed brochures.**
 - f. **ISO 9001 and ISO 14001 certificates of manufacturer.**
 - g. **Test certificates showing compliance with ISO 20957-1 and EN 957-2**
7. **Disqualification.** Offers are liable to be rejected if:-
 - a. Validity of offer is not quoted as required in tender documents.
 - b. **Firm will not provide OEM Authorization Certificate.**
 - c. Any deviation from the general/ special instruction.
 - d. Offers are found conditional or incomplete in any respect.
 - e. Offer is received after fixed date and time on EPADS.

- f. Offers (financial/technical) containing non-signed & stamped unauthenticated amendments/ corrections/overwriting.
 - g. If the offer is found to be based on cartel action in connivance with other sources/participants of the tender.
- 8. **Bid Security** Financial offer must be accompanied with a bid security (CDR/Pay order/Bank draft) in agreement of faithful compliance of the conditions of Contract. This amount will be equivalent to **3%** of the total quoted value. The bid security amount submitted by the successful bidder will however be refunded on effective termination of Contract. The bid security will be forfeited in case of default by the bidder from his commitments made through his offer. Submission of bid security is mandatory; otherwise your offer will be rejected. **Bid security will be used as performance guarantee.**
- 9. **Return of Bid Security**
 - a. Bid security to the unsuccessful bidders will be returned on finalization of the most advantageous bidder.
 - b. Bid security of the successful bidder/bidders will be returned as mentioned in clause 8 above.
- 10. **Terms of Payment**

In FOR cases

- a. Payment shall be made after satisfactory delivery & acceptance of supply with in **25-30 days.**
 - b. No Advance payment shall be made.
 - c. Deductions may apply for non-conforming items or short deliveries.
- 11. **Taxes/ Duties/ Custom clearance** All taxes /duties fee as applicable under government laws in Pakistan as well as country of supplier shall be on seller.
- 12. **Freight charges /Misc charges:** All charges such as packing, forwarding, local freight, loading and unloading, installation and commissioning, custom clearance, orientations, on job training or any other will be part of quoted price. Delivery till ISLAMABAD CLUB will be seller's responsibility and all associated costs will be part of quotation as well.
- 13. **Delivery Period.** Contracted Items will be delivered **45-60 Days** after contract signing date. Deliveries must be accompanied authorized personnel.
- 14. **Scope of Delivery:** The bidder shall Deliver in **45-60 Days** after the Contract Signing as per quantities and types specified in Scope of Work in tender documents and contracts.
- 15. **Force Majeure.** If non-compliance with the period of delivery or services can be proved to be due to Force Majeure, such as but not limited to mobilization, war, riot, strike, lockout, pandemics/epidemics or the occurrence of unforeseen events, the period shall be reasonably extended.

16. **Subletting** Suppliers are not allowed to sublet wholly or part of the contract to any other firm /company. Firm found in breach of the clause will be dealt with as per purchaser's right and discretion.
17. **Arbitration.** Will be as under: -
"All Claims, disputes, controversies, differences arising out of or in connection with this contract, including any question regarding its existence, validity, interpretation performance, breach or termination, shall be referred to and shall finally be solved by binding arbitration. An arbitration committee shall be constituted comprising Secretary Islamabad Club and two arbitrations to be nominated on mutual agreement by each party. The venue of the Arbitration shall be the place of issuance of this contract or as Secretary Islamabad Club may determine. In case of any difference, decision of the Administrator Islamabad Club shall be final and binding on both parties.
Provided that written record of any such arbitration and its award shall be arranged properly.
18. **Redress of Grievance.** In case of dispute, case shall be reviewed by Islamabad Club Redress of grievance committee and its decision shall be final and binding on both parties.
19. **Requirement of Samples/Broachers .** Samples/Broachers must be provided for evaluation by technical authorities with technical offer.
- 20 **Inspection /Testing of Delivery** Inspection & testing will be carried out at Islamabad Club by the concerned inspection team as detailed by the respective department in accordance with the laid down Acceptance criteria as provided in this document, Annexures & quantities given in purchase order.
21. **Checking of deliveries at Consignee/User End.** All deliveries will be inspected/checked at Consignee's end in the presence of the supplier's representative. If for some reason, the supplier decides not to nominate his representative for such checking, an advance written notice to this effect will be given by the supplier to the consignee prior to shipment of items. In such an event the supplier will clearly undertake that decision of consignee with regard to quantities and description of consignment will be taken as final and discrepancy found will be accordingly made up by supplier.
22. **Damage to Property/ Safety Rules.** The contractor/supplier must ensure strict adherence to safety protocols throughout the execution of the work. Any damage to Islamabad Club property resulting from contractor's negligence or misconduct shall be repaired or compensated at the contractor's expense.
23. **General Instructions:** Following must be noted: -
a. The firm should provide point to point acceptance of each clause of tender documents and special instructions attached with tender documents.

- b. Firm will render a certificate with technical offer that firm is neither defaulter nor
blacklisted by any government / semi government organization directly or indirectly. (On Judicial Paper)
- c. Rates should be quoted on free delivery basis at Islamabad Club, Islamabad.
- d. The stipulated delivery period should be strictly adhered to. If the seller fails to deliver the required stores, the buyer will be at liberty to cancel the contract, and /or procure the of stores from an alternate source, on the seller's "Risk & Cost/Expense". In that case, the seller will be bound to make payment to the new source through Islamabad Club. The purchaser's decision under this clause shall currency/execution/after placement if the firm is found to be involved in any dubious activity, litigation, lacking to meet contractual obligations with the purchaser or is blacklisted with any other public procurement agency. No claims / loss /damage of whatsoever nature shall be entertained and Islamabad Club's NOT be subjected to arbitration.
- e. Islamabad Club reserves the right to cancel the contract without assigning any reason whatsoever during its decision in this regard will be final / binding on the seller.
- f. An appropriate amount may be paid for mobilization against CDR/DD/Pay Order.
- g. Firms with previous pending/outstanding projects/business and unsatisfactory performance with Islamabad Club may not be considered for award of any further business.
- h. Most Advantageous Bidder must send their authorized representatives (with authorization letter) for signing of the contract within three days of sharing of the draft contract.
- i. For technical opening firm will send a representative who has knowledge about the quoted items otherwise representative will not be allowed to sit in tender opening.
- j. Samples/Broachers shall be duly marked and packed will be Evaluated by the Technical Evaluation Committee.
- k. Tender will be awarded on package deal basis.

Technical Specifications

IC / SCM / / 2025/26 /Procurement & Installation of Gym Equipment TD- 32

SR	Item	Specification			Quantity	Bidder Compliance	
						YES	NO
1	Plate-Loaded Lateral Raise Machine	Functional & Performance Requirements			1		
		No. 1	Parameter Movement Type	Requirement Shoulder abduction (lateral raise), unilateral or bilateral, with converging motion arms.			
		2	Resistance System	Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.			
		3	Range of Motion	Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.			
		4	Starting Position Adjustment	Minimum 5 indexed start positions with laser-etched markings.			
		5	Counterbalance	Arms or levers to include counterbalance reducing start resistance ≤2 kg.			
		6	Seat & Pad Adjustability	Gas-assisted or precision pop-pin system, seat height range 400–550 mm.			
		7	Tolerance of Resistance	≤ ±1% variance in resistance across full motion path verified by factory test report.			
		8	Noise Level	Operational noise <50			

			dB under dynamic load conditions.			
Construction & Materials						
No.	Parameter	Requirement				
1	Frame	Main frame from 4 mm heavy-duty steel tubing (ASTM A500 Grade B), robot-welded, one-piece design at primary load points.				
2	Finish	Dual-layer electrostatic powder coat with epoxy primer; corrosion tested per ASTM B117 ≥ 1000 -hour salt spray.				
3	Bearings	Sealed self-aligning bearings at all pivot points; bronze bushings not acceptable.				
4	Load Horns	Solid stainless steel Ø50 mm, min. 250 mm loadable length per horn.				
5	Fasteners	All fasteners stainless steel or zinc-plated, metric grade 8.8 or higher.				
6	Upholstery	Injection-molded, high-density foam ≥ 60 kg/m ³ , double-stitched, sweat- and tear-resistant vinyl.				
7	Rubber Feet / End Caps	Non-marking, floor-protective rubber caps at all contact points.				
Safety & Compliance						
No.	Parameter	Requirement				
1	Standards Compliance	Must comply with ISO 20957-1:2013 (Class S) and EN				

		<p>2 Manufacturer Certification</p> <p>3 Factory Testing</p> <p>4 Surface Quality</p> <p>5 Marking</p> <p>6 Documentation</p>	<p>957-2:2015 for stationary strength equipment. Manufacturer shall be ISO 9001 and ISO 14001 certified.</p> <p>Each unit must undergo static and dynamic load testing to 250% rated load. No weld spatter, sharp edges, or misalignment permitted; finish inspected to ISO 8501-3 Grade P3. Permanent serial number, load rating, and model identification on each unit.</p> <p>Third-party test certificate or declaration of conformity for each model must accompany the bid.</p>			
2		<p>Functional & Performance Requirements</p> <p>No. 1 Parameter Movement Type</p> <p>2 Resistance System</p> <p>3 Range of Motion</p>	<p>Requirement Chest press movement in flat position with independent loading arms for balanced strength training. Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range. Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195</p>	1		

	Flat Bench Press Plate-Loaded	4	Starting Position Adjustment	cm height. Minimum 5 indexed start positions with laser-etched markings.			
		5	Counterbalance	Arms or levers to include counterbalance reducing start resistance ≤ 2 kg.			
		6	Seat & Pad Adjustability	Gas-assisted or precision pop-pin system, seat height range 400–550 mm.			
		7	Tolerance of Resistance	$\leq \pm 1\%$ variance in resistance across full motion path verified by factory test report.			
		8	Noise Level	Operational noise ≤ 50 dB under dynamic load conditions.			
		Construction & Materials					
		No.	Parameter	Requirement			
		1	Frame	Main frame from 4 mm heavy-duty steel tubing (ASTM A500 Grade B), robot-welded, one-piece design at primary load points.			
		2	Finish	Dual-layer electrostatic powder coat with epoxy primer; corrosion tested per ASTM B117 ≥ 1000 -hour salt spray.			
		3	Bearings	Sealed self-aligning bearings at all pivot points; bronze bushings not acceptable.			
		4	Load Horns	Solid stainless steel $\varnothing 50$ mm, min. 250 mm loadable length per horn.			
		5	Fasteners	All fasteners stainless			

		6	Upholstery	steel or zinc-plated, metric grade 8.8 or higher. Injection-molded, high-density foam $\geq 60 \text{ kg/m}^3$, double-stitched, sweat- and tear-resistant vinyl.			
		7	Rubber Feet / End Caps	Non-marking, floor-protective rubber caps at all contact points.			
		Safety & Compliance					
		No.	Parameter	Requirement			
		1	Standards Compliance	Must comply with ISO 20957-1:2013 (Class S) and EN 957-2:2015 for stationary strength equipment.			
		2	Manufacturer Certification	Manufacturer shall be ISO 9001 and ISO 14001 certified.			
		3	Factory Testing	Each unit must undergo static and dynamic load testing to 250% rated load.			
		4	Surface Quality	No weld spatter, sharp edges, or misalignment permitted; finish inspected to ISO 8501-3 Grade P3.			
		5	Marking	Permanent serial number, load rating, and model identification on each unit.			
		6	Documentation	Third-party test certificate or declaration of conformity for each model must accompany the bid.			

3	<u>Incline Bench Press Plate-Loaded</u>	Functional & Performance Requirements			1		
		No.	Parameter	Requirement			
		1	Movement Type	Chest press movement in incline position targeting upper pectorals with independent arms.			
		2	Resistance System	Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.			
		3	Range of Motion	Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.			
		4	Starting Position Adjustment	Minimum 5 indexed start positions with laser-etched markings.			
		5	Counterbalance	Arms or levers to include counterbalance reducing start resistance ≤2 kg.			
		6	Seat & Pad Adjustability	Gas-assisted or precision pop-pin system, seat height range 400–550 mm.			
		7	Tolerance of Resistance	≤ ±1% variance in resistance across full motion path verified by factory test report.			
		8	Noise Level	Operational noise ≤50 dB under dynamic load conditions.			
		Construction & Materials					
		No.	Parameter	Requirement			
		1	Frame	Main frame from 4 mm heavy-duty steel tubing (ASTM A500 Grade B), robot-welded, one-piece			

		2	Finish	design at primary load points. Dual-layer electrostatic powder coat with epoxy primer; corrosion tested per ASTM B117 ≥ 1000 -hour salt spray.			
		3	Bearings	Sealed self-aligning bearings at all pivot points; bronze bushings not acceptable.			
		4	Load Horns	Solid stainless steel $\varnothing 50$ mm, min. 250 mm loadable length per horn.			
		5	Fasteners	All fasteners stainless steel or zinc-plated, metric grade 8.8 or higher.			
		6	Upholstery	Injection-molded, high-density foam ≥ 60 kg/m ³ , double-stitched, sweat- and tear-resistant vinyl.			
		7	Rubber Feet / End Caps	Non-marking, floor-protective rubber caps at all contact points.			
		Safety & Compliance					
		No.	Parameter	Requirement			
		1	Standards Compliance	Must comply with ISO 20957-1:2013 (Class S) and EN 957-2:2015 for stationary strength equipment.			
		2	Manufacturer Certification	Manufacturer shall be ISO 9001 and ISO 14001 certified.			
		3	Factory Testing	Each unit must undergo static and dynamic load testing to 250% rated load.			

		4	Surface Quality	No weld spatter, sharp edges, or misalignment permitted; finish inspected to ISO 8501-3 Grade P3.																								
		5	Marking	Permanent serial number, load rating, and model identification on each unit.																								
		6	Documentation	Third-party test certificate or declaration of conformity for each model must accompany the bid.																								
4	Decline Bench Press Plate-Loaded	Functional & Performance Requirements <table><thead><tr><th>No.</th><th>Parameter</th><th>Requirement</th></tr></thead><tbody><tr><td>1</td><td>Movement Type</td><td>Chest press movement in decline position targeting lower pectorals with independent arms.</td></tr><tr><td>2</td><td>Resistance System</td><td>Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.</td></tr><tr><td>3</td><td>Range of Motion</td><td>Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.</td></tr><tr><td>4</td><td>Starting Position Adjustment</td><td>Minimum 5 indexed start positions with laser-etched markings.</td></tr><tr><td>5</td><td>Counterbalance</td><td>Arms or levers to include counterbalance reducing start resistance ≤ 2 kg.</td></tr><tr><td>6</td><td>Seat & Pad Adjustability</td><td>Gas-assisted or precision pop-pin</td></tr></tbody></table>			No.	Parameter	Requirement	1	Movement Type	Chest press movement in decline position targeting lower pectorals with independent arms.	2	Resistance System	Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.	3	Range of Motion	Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.	4	Starting Position Adjustment	Minimum 5 indexed start positions with laser-etched markings.	5	Counterbalance	Arms or levers to include counterbalance reducing start resistance ≤ 2 kg.	6	Seat & Pad Adjustability	Gas-assisted or precision pop-pin	1		
No.	Parameter	Requirement																										
1	Movement Type	Chest press movement in decline position targeting lower pectorals with independent arms.																										
2	Resistance System	Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.																										
3	Range of Motion	Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.																										
4	Starting Position Adjustment	Minimum 5 indexed start positions with laser-etched markings.																										
5	Counterbalance	Arms or levers to include counterbalance reducing start resistance ≤ 2 kg.																										
6	Seat & Pad Adjustability	Gas-assisted or precision pop-pin																										

		7	Tolerance of Resistance	system, seat height range 400–550 mm. $\leq \pm 1\%$ variance in resistance across full motion path verified by factory test report.			
		8	Noise Level	Operational noise ≤ 50 dB under dynamic load conditions.			
		Construction & Materials					
		No.	Parameter	Requirement			
		1	Frame	Main frame from 4 mm heavy-duty steel tubing (ASTM A500 Grade B), robot-welded, one-piece design at primary load points.			
		2	Finish	Dual-layer electrostatic powder coat with epoxy primer; corrosion tested per ASTM B117 ≥ 1000 -hour salt spray.			
		3	Bearings	Sealed self-aligning bearings at all pivot points; bronze bushings not acceptable.			
		4	Load Horns	Solid stainless steel $\varnothing 50$ mm, min. 250 mm loadable length per horn.			
		5	Fasteners	All fasteners stainless steel or zinc-plated, metric grade 8.8 or higher.			
		6	Upholstery	Injection-molded, high-density foam ≥ 60 kg/m ³ , double-stitched, sweat- and tear-resistant vinyl.			
		7	Rubber Feet / End Caps	Non-marking, floor-protective rubber caps			

		<div>at all contact points.</div> <div>Safety & Compliance</div> <table><tr><th>No.</th><th>Parameter</th><th>Requirement</th></tr><tr><td>1</td><td>Standards Compliance</td><td>Must comply with ISO 20957-1:2013 (Class S) and EN 957-2:2015 for stationary strength equipment.</td></tr><tr><td>2</td><td>Manufacturer Certification</td><td>Manufacturer shall be ISO 9001 and ISO 14001 certified.</td></tr><tr><td>3</td><td>Factory Testing</td><td>Each unit must undergo static and dynamic load testing to 250% rated load.</td></tr><tr><td>4</td><td>Surface Quality</td><td>No weld spatter, sharp edges, or misalignment permitted; finish inspected to ISO 8501-3 Grade P3.</td></tr><tr><td>5</td><td>Marking</td><td>Permanent serial number, load rating, and model identification on each unit.</td></tr><tr><td>6</td><td>Documentation</td><td>Third-party test certificate or declaration of conformity for each model must accompany the bid.</td></tr></table>	No.	Parameter	Requirement	1	Standards Compliance	Must comply with ISO 20957-1:2013 (Class S) and EN 957-2:2015 for stationary strength equipment.	2	Manufacturer Certification	Manufacturer shall be ISO 9001 and ISO 14001 certified.	3	Factory Testing	Each unit must undergo static and dynamic load testing to 250% rated load.	4	Surface Quality	No weld spatter, sharp edges, or misalignment permitted; finish inspected to ISO 8501-3 Grade P3.	5	Marking	Permanent serial number, load rating, and model identification on each unit.	6	Documentation	Third-party test certificate or declaration of conformity for each model must accompany the bid.			
No.	Parameter	Requirement																								
1	Standards Compliance	Must comply with ISO 20957-1:2013 (Class S) and EN 957-2:2015 for stationary strength equipment.																								
2	Manufacturer Certification	Manufacturer shall be ISO 9001 and ISO 14001 certified.																								
3	Factory Testing	Each unit must undergo static and dynamic load testing to 250% rated load.																								
4	Surface Quality	No weld spatter, sharp edges, or misalignment permitted; finish inspected to ISO 8501-3 Grade P3.																								
5	Marking	Permanent serial number, load rating, and model identification on each unit.																								
6	Documentation	Third-party test certificate or declaration of conformity for each model must accompany the bid.																								
		<div>Functional & Performance Requirements</div> <table><tr><th>No.</th><th>Parameter</th><th>Requirement</th></tr><tr><td>1</td><td>Machine Type</td><td>Dual-function Pectoral Fly / Rear Deltoid, selectorized with independent rotating arms.</td></tr><tr><td>2</td><td>Resistance System</td><td>Weight-stack type with fully enclosed housing, standard 260 lb (118 kg), heavy up</td></tr></table>	No.	Parameter	Requirement	1	Machine Type	Dual-function Pectoral Fly / Rear Deltoid, selectorized with independent rotating arms.	2	Resistance System	Weight-stack type with fully enclosed housing, standard 260 lb (118 kg), heavy up															
No.	Parameter	Requirement																								
1	Machine Type	Dual-function Pectoral Fly / Rear Deltoid, selectorized with independent rotating arms.																								
2	Resistance System	Weight-stack type with fully enclosed housing, standard 260 lb (118 kg), heavy up																								

5	Pec Deck Fly Machine	3	Resistance Profile	to 305 lb (138 kg). Independent cam geometry providing variable resistance curve matching fly motion.	1		
		4	Handle Design	Pivoting, self-aligning dual-axis handles with high-density thermoplastic overmold.			
		5	Adjustability	Gas-assisted seat (4+ positions), ROM adjustment (6 positions).			
		6	User Capacity	Minimum 181 kg (400 lb).			
		7	Dimensions	Max 157 cm W × 99 cm D × 237 cm H (±5%)..			
		8	Machine Weight	260 – 320 kg total.			
		Construction & Materials					
		No.	Parameter	Requirement			
		1	Frame	11-gauge (3 mm) welded steel, 2×4 in. rectangular tubing, electrostatic powder coat.			
		2	Finish	Molded shrouds, smooth contours, silver/graphite frame, black upholstery.			
		3	Cable System	7×19-strand nylon-coated steel cable, ≥1,800 kg tensile strength.			
		4	Pulley System	Fiberglass-reinforced pulleys with sealed bearings, ≥100 mm diameter.			
		5	Seat & Back Pad	High-density foam (≥65 kg/m³), marine-grade vinyl upholstery.			
		6	Instruction Placard	Integrated pictorial			

		<div>7</div> <div>Noise & Smoothness</div> <div>placard showing setup and muscle groups. ≤60 dB during operation, continuous motion.</div>																					
		<div>Safety & Compliance</div> <table><tr><td>No.</td><td>Parameter</td><td>Requirement</td></tr><tr><td>1</td><td>Standards Compliance</td><td>Comply with EN 957-1/2 or ASTM F2216-22.</td></tr><tr><td>2</td><td>Manufacturer Certification</td><td>Manufacturer shall be ISO 9001 and ISO 14001 certified.</td></tr><tr><td>3</td><td>Documentation</td><td>Third-party test certificate or declaration of conformity for each model must accompany the bid.</td></tr></table>	No.	Parameter	Requirement	1	Standards Compliance	Comply with EN 957-1/2 or ASTM F2216-22.	2	Manufacturer Certification	Manufacturer shall be ISO 9001 and ISO 14001 certified.	3	Documentation	Third-party test certificate or declaration of conformity for each model must accompany the bid.									
No.	Parameter	Requirement																					
1	Standards Compliance	Comply with EN 957-1/2 or ASTM F2216-22.																					
2	Manufacturer Certification	Manufacturer shall be ISO 9001 and ISO 14001 certified.																					
3	Documentation	Third-party test certificate or declaration of conformity for each model must accompany the bid.																					
6	Triceps Press Machine Plate-Loaded	<div>Functional & Performance Requirements</div> <table><tr><td>No.</td><td>Parameter</td><td>Requirement</td></tr><tr><td>1</td><td>Movement Type</td><td>Seated triceps extension/press motion with independent converging arms.</td></tr><tr><td>2</td><td>Resistance System</td><td>Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.</td></tr><tr><td>3</td><td>Range of Motion</td><td>Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.</td></tr><tr><td>4</td><td>Starting Position Adjustment</td><td>Minimum 5 indexed start positions with laser-etched markings.</td></tr><tr><td>5</td><td>Counterbalance</td><td>Arms or levers to include counterbalance reducing start resistance ≤2 kg.</td></tr></table>	No.	Parameter	Requirement	1	Movement Type	Seated triceps extension/press motion with independent converging arms.	2	Resistance System	Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.	3	Range of Motion	Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.	4	Starting Position Adjustment	Minimum 5 indexed start positions with laser-etched markings.	5	Counterbalance	Arms or levers to include counterbalance reducing start resistance ≤2 kg.	1		
No.	Parameter	Requirement																					
1	Movement Type	Seated triceps extension/press motion with independent converging arms.																					
2	Resistance System	Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.																					
3	Range of Motion	Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.																					
4	Starting Position Adjustment	Minimum 5 indexed start positions with laser-etched markings.																					
5	Counterbalance	Arms or levers to include counterbalance reducing start resistance ≤2 kg.																					

		6	Seat & Pad Adjustability	Gas-assisted or precision pop-pin system, seat height range 400–550 mm.			
		7	Tolerance of Resistance	$\leq \pm 1\%$ variance in resistance across full motion path verified by factory test report.			
		8	Noise Level	Operational noise ≤ 50 dB under dynamic load conditions.			
		Construction & Materials					
		No.	Parameter	Requirement			
		1	Frame	Main frame from 4 mm heavy-duty steel tubing (ASTM A500 Grade B), robot-welded, one-piece design at primary load points.			
		2	Finish	Dual-layer electrostatic powder coat with epoxy primer; corrosion tested per ASTM B117 ≥ 1000 -hour salt spray.			
		3	Bearings	Sealed self-aligning bearings at all pivot points; bronze bushings not acceptable.			
		4	Load Horns	Solid stainless steel $\varnothing 50$ mm, min. 250 mm loadable length per horn.			
		5	Fasteners	All fasteners stainless steel or zinc-plated, metric grade 8.8 or higher.			
		6	Upholstery	Injection-molded, high-density foam ≥ 60 kg/m ³ , double-stitched, sweat- and tear-resistant vinyl.			

		7	Rubber Feet / End Caps	Non-marking, floor-protective rubber caps at all contact points.			
		Safety & Compliance					
		No.	Parameter	Requirement			
		1	Standards Compliance	Must comply with ISO 20957-1:2013 (Class S) and EN 957-2:2015 for stationary strength equipment.			
		2	Manufacturer Certification	Manufacturer shall be ISO 9001 and ISO 14001 certified.			
		3	Factory Testing	Each unit must undergo static and dynamic load testing to 250% rated load.			
		4	Surface Quality	No weld spatter, sharp edges, or misalignment permitted; finish inspected to ISO 8501-3 Grade P3.			
		5	Marking	Permanent serial number, load rating, and model identification on each unit.			
		6	Documentation	Third-party test certificate or declaration of conformity for each model must accompany the bid.			

7	Assisted Pull-Up Machine	Functional & Performance Requirements			1		
		No.	Parameter	Required Specification			
		1	Machine Type	Dual-function Assisted Pull-Up / Dip, selectorized counterbalance with rotating/foldable knee pad.			
		2	Resistance System	Selectorized weight stack enclosed by shrouds, standard 200 lb (91 kg) min, heavy stack up to 295 lb (134 kg).			
		3	Assistance Platform	Counterbalanced knee pad folds or rotates away for unassisted exercises; smooth linear bushings.			
		4	Frame Construction	11-gauge (3 mm) welded steel tubing, 2×4 in. rectangular/oval, powder-coated double-baked finish.			
		5	Handles	Multi-grip ergonomically angled handles with non-slip textured overmold grips for pull-up and dip.			
		6	Step Design	Two-level non-slip access steps made of die-cast or molded rubber with steel reinforcement.			
		7	Adjustments	Knee pad fold-away mechanism with gas-assist/torsion spring, one-hand operation.			
		8	Dimensions	Width ≤132 cm, Depth ≤140 cm, Height ≤232 cm (±5%).			

		9	Machine Weight	270–310 kg total.			
		10	User Capacity	Support at least 181 kg (400 lb).			
		11	Cables	7×19-strand nylon-coated steel cable rated $\geq 1,800$ kg tensile strength, pulleys ≥ 100 mm with sealed bearings.			
		12	Bearings & Movement	Linear bearings ensuring smooth, quiet (<60 dB) operation throughout ROM.			
		13	Seat/Pads/Upholstery	High-density foam ≥ 65 kg/m ³ with marine-grade vinyl upholstery and double stitching.			
		14	Instruction Placard	Integrated pictorial exercise instruction placard showing muscles and setup.			
		15	Finish & Design	Shrouded weight stack, rounded frame corners, silver/graphite finish, black upholstery.			
		16	Safety Certification	Comply with EN 957-1/2 or ASTM F2216-22.			
		17	Origin	Manufactured in ISO 9001 & ISO 14001 certified facility.			
		18	Documentation	Include Operation Manual, Maintenance Manual, and Parts Catalog.			

Evaluation Criteria

Sr.	Description	Marks/percentage
1	Compliance with functional and performance requirements	40%
2	Compliance with ISO / EN standards and test certification	20%
3	Construction quality and material Specifications	20%
4	Warranty and after-sales service in Pakistan	10%
5	Delivery and installation capability	10%

Only bidders achieving at least 80% compliance in technical evaluation will proceed to financial evaluation.

Firm Name: _____
Signature: _____
Name: _____
Designation: _____

Necessary to Fill Completely**Fill in following essential Parameters: -**

1.	Validity of Offer	Days (Should not be less than 120 days)	
2.	Delivery period	Days (After placement of order)	

General: -

1.	GST Number	Enclose Copy
2.	NTN / CNIC	if exempted, provide valid exemption certificate

Payment Terms (In continuation of Tender Document clause 12): -

In FOR Cases
<ul style="list-style-type: none">a. Payment shall be made after satisfactory delivery & acceptance of supply.b. No Advance payment shall be made.c. Deductions may apply for non-conforming items or short deliveries.
Samples must be properly presented Name and number of Focal Person Bank Details for confirmation of Earnest Money (Mandatory) Installation, Commissioning of Gym Equipments will be Vendors Responsibility

FINANCIAL OFFER**IC / SCM / Procurement & Installation of Gym Equipment / 2025/26 / TD-32**

SR	Item	Specification	Quantity	Unit Price PKR (Including Tax)	Total Price PKR (Including Tax)	
1	Plate-Loaded Lateral Raise Machine	Functional & Performance Requirements				
		No.	Parameter	Requirement		
		1	Movement Type	Shoulder abduction (lateral raise), unilateral or bilateral, with converging motion arms.		
		2	Resistance System	Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.		
		3	Range of Motion	Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.		
		4	Starting Position Adjustment	Minimum 5 indexed start positions with laser-etched markings.		
		5	Counterbalance	Arms or levers to include counterbalance reducing start resistance ≤2 kg.		
		6	Seat & Pad Adjustability	Gas-assisted or precision pop-pin system, seat height range 400–550 mm.		
7	Tolerance of Resistance	≤ ±1% variance in resistance across full motion path verified				

		8	Noise Level	by factory test report. Operational noise ≤50 dB under dynamic load conditions.			
		Construction & Materials					
		No.	Parameter	Requirement			
		1	Frame	Main frame from 4 mm heavy-duty steel tubing (ASTM A500 Grade B), robot-welded, one-piece design at primary load points.			
		2	Finish	Dual-layer electrostatic powder coat with epoxy primer; corrosion tested per ASTM B117 ≥1000-hour salt spray.			
		3	Bearings	Sealed self-aligning bearings at all pivot points; bronze bushings not acceptable.			
		4	Load Horns	Solid stainless steel Ø50 mm, min. 250 mm loadable length per horn.			
		5	Fasteners	All fasteners stainless steel or zinc-plated, metric grade 8.8 or higher.			
		6	Upholstery	Injection-molded, high-density foam ≥60 kg/m³, double-stitched, sweat- and tear-resistant vinyl.			
		7	Rubber Feet / End Caps	Non-marking, floor-protective rubber caps at all contact points.			
		Safety & Compliance					
		No.	Parameter	Requirement			

		1	Standards Compliance	Must comply with ISO 20957-1:2013 (Class S) and EN 957-2:2015 for stationary strength equipment.			
		2	Manufacturer Certification	Manufacturer shall be ISO 9001 and ISO 14001 certified.			
		3	Factory Testing	Each unit must undergo static and dynamic load testing to 250% rated load.			
		4	Surface Quality	No weld spatter, sharp edges, or misalignment permitted; finish inspected to ISO 8501-3 Grade P3.			
		5	Marking	Permanent serial number, load rating, and model identification on each unit.			
		6	Documentation	Third-party test certificate or declaration of conformity for each model must accompany the bid.			
2		Functional & Performance Requirements					
		No. 1	Parameter Movement Type	Requirement Chest press movement in flat position with independent loading arms for balanced strength training.			
		2	Resistance System	Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.	1		
		3	Range of Motion	Biomechanically validated to ISO			

	Flat Bench Press Plate-Loaded	4	Starting Position Adjustment	20957-1 Class S and EN 957-2, covering users from 150–195 cm height.			
		5	Counterbalance	Minimum 5 indexed start positions with laser-etched markings. Arms or levers to include counterbalance reducing start resistance ≤ 2 kg.			
		6	Seat & Pad Adjustability	Gas-assisted or precision pop-pin system, seat height range 400–550 mm.			
		7	Tolerance of Resistance	$\leq \pm 1\%$ variance in resistance across full motion path verified by factory test report.			
		8	Noise Level	Operational noise ≤ 50 dB under dynamic load conditions.			
		Construction & Materials					
		No.	Parameter	Requirement			
		1	Frame	Main frame from 4 mm heavy-duty steel tubing (ASTM A500 Grade B), robot-welded, one-piece design at primary load points.			
		2	Finish	Dual-layer electrostatic powder coat with epoxy primer; corrosion tested per ASTM B117 ≥ 1000 -hour salt spray.			
		3	Bearings	Sealed self-aligning bearings at all pivot points; bronze bushings not acceptable.			
		4	Load Horns	Solid stainless steel $\varnothing 50$ mm, min. 250			

		5	Fasteners	mm loadable length per horn. All fasteners stainless steel or zinc-plated, metric grade 8.8 or higher.			
		6	Upholstery	Injection-molded, high-density foam $\geq 60 \text{ kg/m}^3$, double-stitched, sweat- and tear-resistant vinyl.			
		7	Rubber Feet / End Caps	Non-marking, floor-protective rubber caps at all contact points.			
		Safety & Compliance					
		No.	Parameter	Requirement			
		1	Standards Compliance	Must comply with ISO 20957-1:2013 (Class S) and EN 957-2:2015 for stationary strength equipment.			
		2	Manufacturer Certification	Manufacturer shall be ISO 9001 and ISO 14001 certified.			
		3	Factory Testing	Each unit must undergo static and dynamic load testing to 250% rated load.			
		4	Surface Quality	No weld spatter, sharp edges, or misalignment permitted; finish inspected to ISO 8501-3 Grade P3.			
		5	Marking	Permanent serial number, load rating, and model identification on each unit.			
		6	Documentation	Third-party test certificate or declaration of conformity for each			

		model must accompany the bid.																																						
3	<u>Incline Bench Press Plate-Loaded</u>	<p>Functional & Performance Requirements</p> <table><thead><tr><th>No.</th><th>Parameter</th><th>Requirement</th></tr></thead><tbody><tr><td>1</td><td>Movement Type</td><td>Chest press movement in incline position targeting upper pectorals with independent arms.</td></tr><tr><td>2</td><td>Resistance System</td><td>Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.</td></tr><tr><td>3</td><td>Range of Motion</td><td>Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.</td></tr><tr><td>4</td><td>Starting Position Adjustment</td><td>Minimum 5 indexed start positions with laser-etched markings.</td></tr><tr><td>5</td><td>Counterbalance</td><td>Arms or levers to include counterbalance reducing start resistance ≤2 kg.</td></tr><tr><td>6</td><td>Seat & Pad Adjustability</td><td>Gas-assisted or precision pop-pin system, seat height range 400–550 mm.</td></tr><tr><td>7</td><td>Tolerance of Resistance</td><td>≤ ±1% variance in resistance across full motion path verified by factory test report.</td></tr><tr><td>8</td><td>Noise Level</td><td>Operational noise ≤50 dB under dynamic load conditions.</td></tr></tbody></table> <p>Construction & Materials</p> <table><thead><tr><th>No.</th><th>Parameter</th><th>Requirement</th></tr></thead><tbody><tr><td>1</td><td>Frame</td><td>Main frame from 4 mm heavy-duty steel</td></tr></tbody></table>			No.	Parameter	Requirement	1	Movement Type	Chest press movement in incline position targeting upper pectorals with independent arms.	2	Resistance System	Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.	3	Range of Motion	Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.	4	Starting Position Adjustment	Minimum 5 indexed start positions with laser-etched markings.	5	Counterbalance	Arms or levers to include counterbalance reducing start resistance ≤2 kg.	6	Seat & Pad Adjustability	Gas-assisted or precision pop-pin system, seat height range 400–550 mm.	7	Tolerance of Resistance	≤ ±1% variance in resistance across full motion path verified by factory test report.	8	Noise Level	Operational noise ≤50 dB under dynamic load conditions.	No.	Parameter	Requirement	1	Frame	Main frame from 4 mm heavy-duty steel	1		
No.	Parameter	Requirement																																						
1	Movement Type	Chest press movement in incline position targeting upper pectorals with independent arms.																																						
2	Resistance System	Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.																																						
3	Range of Motion	Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.																																						
4	Starting Position Adjustment	Minimum 5 indexed start positions with laser-etched markings.																																						
5	Counterbalance	Arms or levers to include counterbalance reducing start resistance ≤2 kg.																																						
6	Seat & Pad Adjustability	Gas-assisted or precision pop-pin system, seat height range 400–550 mm.																																						
7	Tolerance of Resistance	≤ ±1% variance in resistance across full motion path verified by factory test report.																																						
8	Noise Level	Operational noise ≤50 dB under dynamic load conditions.																																						
No.	Parameter	Requirement																																						
1	Frame	Main frame from 4 mm heavy-duty steel																																						

		2	Finish	tubing (ASTM A500 Grade B), robot-welded, one-piece design at primary load points. Dual-layer electrostatic powder coat with epoxy primer; corrosion tested per ASTM B117 ≥ 1000 -hour salt spray.			
		3	Bearings	Sealed self-aligning bearings at all pivot points; bronze bushings not acceptable.			
		4	Load Horns	Solid stainless steel $\varnothing 50$ mm, min. 250 mm loadable length per horn.			
		5	Fasteners	All fasteners stainless steel or zinc-plated, metric grade 8.8 or higher.			
		6	Upholstery	Injection-molded, high-density foam ≥ 60 kg/m ³ , double-stitched, sweat- and tear-resistant vinyl.			
		7	Rubber Feet / End Caps	Non-marking, floor-protective rubber caps at all contact points.			
		Safety & Compliance					
		No. 1	Parameter Standards Compliance	Requirement Must comply with ISO 20957-1:2013 (Class S) and EN 957-2:2015 for stationary strength equipment.			
		2	Manufacturer Certification	Manufacturer shall be ISO 9001 and ISO 14001 certified.			

		3	Factory Testing	Each unit must undergo static and dynamic load testing to 250% rated load.																					
		4	Surface Quality	No weld spatter, sharp edges, or misalignment permitted; finish inspected to ISO 8501-3 Grade P3.																					
		5	Marking	Permanent serial number, load rating, and model identification on each unit.																					
		6	Documentation	Third-party test certificate or declaration of conformity for each model must accompany the bid.																					
4	Decline Bench Press Plate-Loaded	Functional & Performance Requirements <table><tr><td>No.</td><td>Parameter</td><td>Requirement</td></tr><tr><td>1</td><td>Movement Type</td><td>Chest press movement in decline position targeting lower pectorals with independent arms.</td></tr><tr><td>2</td><td>Resistance System</td><td>Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.</td></tr><tr><td>3</td><td>Range of Motion</td><td>Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.</td></tr><tr><td>4</td><td>Starting Position Adjustment</td><td>Minimum 5 indexed start positions with laser-etched markings.</td></tr><tr><td>5</td><td>Counterbalance</td><td>Arms or levers to include counterbalance</td></tr></table>			No.	Parameter	Requirement	1	Movement Type	Chest press movement in decline position targeting lower pectorals with independent arms.	2	Resistance System	Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.	3	Range of Motion	Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.	4	Starting Position Adjustment	Minimum 5 indexed start positions with laser-etched markings.	5	Counterbalance	Arms or levers to include counterbalance	1		
No.	Parameter	Requirement																							
1	Movement Type	Chest press movement in decline position targeting lower pectorals with independent arms.																							
2	Resistance System	Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.																							
3	Range of Motion	Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.																							
4	Starting Position Adjustment	Minimum 5 indexed start positions with laser-etched markings.																							
5	Counterbalance	Arms or levers to include counterbalance																							

		6	Seat & Pad Adjustability	reducing start resistance ≤ 2 kg. Gas-assisted or precision pop-pin system, seat height range 400–550 mm.			
		7	Tolerance of Resistance	$\leq \pm 1\%$ variance in resistance across full motion path verified by factory test report.			
		8	Noise Level	Operational noise ≤ 50 dB under dynamic load conditions.			
		Construction & Materials					
		No.	Parameter	Requirement			
		1	Frame	Main frame from 4 mm heavy-duty steel tubing (ASTM A500 Grade B), robot-welded, one-piece design at primary load points.			
		2	Finish	Dual-layer electrostatic powder coat with epoxy primer; corrosion tested per ASTM B117 ≥ 1000 -hour salt spray.			
		3	Bearings	Sealed self-aligning bearings at all pivot points; bronze bushings not acceptable.			
		4	Load Horns	Solid stainless steel $\varnothing 50$ mm, min. 250 mm loadable length per horn.			
		5	Fasteners	All fasteners stainless steel or zinc-plated, metric grade 8.8 or higher.			
		6	Upholstery	Injection-molded, high-density foam ≥ 60 kg/m ³ , double-			

		<div>7</div> <div>Rubber Feet / End Caps</div> <div>stitched, sweat- and tear-resistant vinyl. Non-marking, floor-protective rubber caps at all contact points.</div>			
		<div>Safety & Compliance</div> <div><div>No.1</div><div>Parameter Standards Compliance</div><div>Requirement Must comply with ISO 20957-1:2013 (Class S) and EN 957-2:2015 for stationary strength equipment.</div></div> <div><div>2</div><div>Manufacturer Certification</div><div>Manufacturer shall be ISO 9001 and ISO 14001 certified.</div></div> <div><div>3</div><div>Factory Testing</div><div>Each unit must undergo static and dynamic load testing to 250% rated load.</div></div> <div><div>4</div><div>Surface Quality</div><div>No weld spatter, sharp edges, or misalignment permitted; finish inspected to ISO 8501-3 Grade P3.</div></div> <div><div>5</div><div>Marking</div><div>Permanent serial number, load rating, and model identification on each unit.</div></div> <div><div>6</div><div>Documentation</div><div>Third-party test certificate or declaration of conformity for each model must accompany the bid.</div></div>			
		<div>Functional & Performance Requirements</div> <div><div>No.1</div><div>Parameter Machine Type</div><div>Requirement Dual-function Pectoral Fly / Rear Deltoid, selectorized with independent</div></div>			

5	Pec Deck Fly Machine	2	Resistance System	rotating arms. Weight-stack type with fully enclosed housing, standard 260 lb (118 kg), heavy up to 305 lb (138 kg).	1		
		3	Resistance Profile	Independent cam geometry providing variable resistance curve matching fly motion.			
		4	Handle Design	Pivoting, self-aligning dual-axis handles with high-density thermoplastic overmold.			
		5	Adjustability	Gas-assisted seat (4+ positions), ROM adjustment (6 positions).			
		6	User Capacity	Minimum 181 kg (400 lb).			
		7	Dimensions	Max 157 cm W × 99 cm D × 237 cm H (±5%)..			
		8	Machine Weight	260 – 320 kg total.			
		Construction & Materials					
		No.	Parameter	Requirement			
		1	Frame	11-gauge (3 mm) welded steel, 2×4 in. rectangular tubing, electrostatic powder coat.			
		2	Finish	Molded shrouds, smooth contours, silver/graphite frame, black upholstery.			
		3	Cable System	7×19-strand nylon-coated steel cable, ≥1,800 kg tensile strength.			
4	Pulley System	Fiberglass-reinforced pulleys with sealed bearings, ≥100 mm diameter.					

		<table><tr><td>5</td><td>Seat & Back Pad</td><td>High-density foam ($\geq 65 \text{ kg/m}^3$), marine-grade vinyl upholstery.</td></tr><tr><td>6</td><td>Instruction Placard</td><td>Integrated pictorial placard showing setup and muscle groups.</td></tr><tr><td>7</td><td>Noise & Smoothness</td><td>$\leq 60 \text{ dB}$ during operation, continuous motion.</td></tr><tr><td colspan="3">Safety & Compliance</td></tr><tr><td>No. 1</td><td>Parameter Standards Compliance</td><td>Requirement Comply with EN 957-1/2 or ASTM F2216-22.</td></tr><tr><td>2</td><td>Manufacturer Certification</td><td>Manufacturer shall be ISO 9001 and ISO 14001 certified.</td></tr><tr><td>3</td><td>Documentation</td><td>Third-party test certificate or declaration of conformity for each model must accompany the bid.</td></tr></table>	5	Seat & Back Pad	High-density foam ($\geq 65 \text{ kg/m}^3$), marine-grade vinyl upholstery.	6	Instruction Placard	Integrated pictorial placard showing setup and muscle groups.	7	Noise & Smoothness	$\leq 60 \text{ dB}$ during operation, continuous motion.	Safety & Compliance			No. 1	Parameter Standards Compliance	Requirement Comply with EN 957-1/2 or ASTM F2216-22.	2	Manufacturer Certification	Manufacturer shall be ISO 9001 and ISO 14001 certified.	3	Documentation	Third-party test certificate or declaration of conformity for each model must accompany the bid.			
5	Seat & Back Pad	High-density foam ($\geq 65 \text{ kg/m}^3$), marine-grade vinyl upholstery.																								
6	Instruction Placard	Integrated pictorial placard showing setup and muscle groups.																								
7	Noise & Smoothness	$\leq 60 \text{ dB}$ during operation, continuous motion.																								
Safety & Compliance																										
No. 1	Parameter Standards Compliance	Requirement Comply with EN 957-1/2 or ASTM F2216-22.																								
2	Manufacturer Certification	Manufacturer shall be ISO 9001 and ISO 14001 certified.																								
3	Documentation	Third-party test certificate or declaration of conformity for each model must accompany the bid.																								
6	Triceps Press Machine Plate-Loaded	<table><tr><td colspan="3">Functional & Performance Requirements</td></tr><tr><td>No. 1</td><td>Parameter Movement Type</td><td>Requirement Seated triceps extension/press motion with independent converging arms.</td></tr><tr><td>2</td><td>Resistance System</td><td>Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.</td></tr><tr><td>3</td><td>Range of Motion</td><td>Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.</td></tr><tr><td>4</td><td>Starting Position Adjustment</td><td>Minimum 5 indexed start positions with</td></tr></table>	Functional & Performance Requirements			No. 1	Parameter Movement Type	Requirement Seated triceps extension/press motion with independent converging arms.	2	Resistance System	Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.	3	Range of Motion	Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.	4	Starting Position Adjustment	Minimum 5 indexed start positions with	1								
Functional & Performance Requirements																										
No. 1	Parameter Movement Type	Requirement Seated triceps extension/press motion with independent converging arms.																								
2	Resistance System	Independent plate-loaded arms with linear or arc motion; smooth and synchronized through full range.																								
3	Range of Motion	Biomechanically validated to ISO 20957-1 Class S and EN 957-2, covering users from 150–195 cm height.																								
4	Starting Position Adjustment	Minimum 5 indexed start positions with																								

		5	Counterbalance	laser-etched markings. Arms or levers to include counterbalance reducing start resistance ≤ 2 kg.			
		6	Seat & Pad Adjustability	Gas-assisted or precision pop-pin system, seat height range 400–550 mm.			
		7	Tolerance of Resistance	$\leq \pm 1\%$ variance in resistance across full motion path verified by factory test report.			
		8	Noise Level	Operational noise ≤ 50 dB under dynamic load conditions.			
		Construction & Materials					
		No.	Parameter	Requirement			
		1	Frame	Main frame from 4 mm heavy-duty steel tubing (ASTM A500 Grade B), robot-welded, one-piece design at primary load points.			
		2	Finish	Dual-layer electrostatic powder coat with epoxy primer; corrosion tested per ASTM B117 ≥ 1000 -hour salt spray.			
		3	Bearings	Sealed self-aligning bearings at all pivot points; bronze bushings not acceptable.			
		4	Load Horns	Solid stainless steel $\varnothing 50$ mm, min. 250 mm loadable length per horn.			
		5	Fasteners	All fasteners stainless steel or zinc-plated, metric grade 8.8 or higher.			

		6	Upholstery	Injection-molded, high-density foam $\geq 60 \text{ kg/m}^3$, double-stitched, sweat- and tear-resistant vinyl.			
		7	Rubber Feet / End Caps	Non-marking, floor-protective rubber caps at all contact points.			
		Safety & Compliance					
		No. 1	Parameter Standards Compliance	Requirement Must comply with ISO 20957-1:2013 (Class S) and EN 957-2:2015 for stationary strength equipment.			
		2	Manufacturer Certification	Manufacturer shall be ISO 9001 and ISO 14001 certified.			
		3	Factory Testing	Each unit must undergo static and dynamic load testing to 250% rated load.			
		4	Surface Quality	No weld spatter, sharp edges, or misalignment permitted; finish inspected to ISO 8501-3 Grade P3.			
		5	Marking	Permanent serial number, load rating, and model identification on each unit.			
		6	Documentation	Third-party test certificate or declaration of conformity for each model must accompany the bid.			
7		Functional & Performance Requirements					
		No.	Parameter	Required Specification			

	Assisted Pull-Up Machine	1	Machine Type	Dual-function Assisted Pull-Up / Dip, selectorized counterbalance with rotating/foldable knee pad.	1		
		2	Resistance System	Selectorized weight stack enclosed by shrouds, standard 200 lb (91 kg) min, heavy stack up to 295 lb (134 kg).			
		3	Assistance Platform	Counterbalanced knee pad folds or rotates away for unassisted exercises; smooth linear bushings.			
		4	Frame Construction	11-gauge (3 mm) welded steel tubing, 2×4 in. rectangular/oval, powder-coated double-baked finish.			
		5	Handles	Multi-grip ergonomically angled handles with non-slip textured overmold grips for pull-up and dip.			
		6	Step Design	Two-level non-slip access steps made of die-cast or molded rubber with steel reinforcement.			
		7	Adjustments	Knee pad fold-away mechanism with gas-assist/torsion spring, one-hand operation.			
		8	Dimensions	Width ≤132 cm, Depth ≤140 cm, Height ≤232 cm (±5%).			
		9	Machine Weight	270–310 kg total.			
		10	User Capacity	Support at least 181 kg (400 lb).			

		11	Cables	7×19-strand nylon-coated steel cable rated $\geq 1,800$ kg tensile strength, pulleys ≥ 100 mm with sealed bearings.			
		12	Bearings & Movement	Linear bearings ensuring smooth, quiet (<60 dB) operation throughout ROM.			
		13	Seat/Pads/Upholstery	High-density foam ≥ 65 kg/m ³ with marine-grade vinyl upholstery and double stitching.			
		14	Instruction Placard	Integrated pictorial exercise instruction placard showing muscles and setup.			
		15	Finish & Design	Shrouded weight stack, rounded frame corners, silver/graphite finish, black upholstery.			
		16	Safety Certification	Comply with EN 957-1/2 or ASTM F2216-22.			
		17	Origin	Manufactured in ISO 9001 & ISO 14001 certified facility.			
		18	Documentation	Include Operation Manual, Maintenance Manual, and Parts Catalog.			

Firm Name: _____
Signature: _____
Name: _____
Designation: _____

Tender No _____

Name of the Firm _____

Firm Address _____

Date _____

Telephone No _____

E-Mail _____

To,

Procurement Consultant

SCM Office

ISLAMABAD

Dear Sir

1. I / We hereby offer to supply to the ISLAMABAD CLUB the stores detailed in schedule to the tender inquiry or such portion thereof as you may specify in the acceptance of tender at the price offered against the said schedule and further agree that this offer will remain valid up to 90 days after opening of Financial offer and will not be withdrawn or altered in terms of rates quoted and the conditions already stated therein or on before this date. I / we shall be bound by a communication of acceptance to be dispatched within the prescribed time.
2. I / we have understood the instructions to Tenders and General Conditions Governing Contract available at ISLAMABAD CLUB website and have thoroughly examined the specifications / drawing and / or patterns quoted in the schedule here to and am/are fully aware of the nature of the stores required and my/ our offer is to supply stores strictly in accordance with the requirements. Yours Faithfully.

(Signature of Tenderer) Designation

Date:

Note: Individual signing tender and / or other documents connected with a contract must be signed by principal authorized rep.

CHECK LIST

(This checked list must be attached with your technical offer, duly filled and Signed by authorized signatory)

Tender No _____

Date _____

1	Tender Fee	a. Tender fee ref no b. Bank c. Amount		
2	Bid Security	a. Bid Security Ref no b. Bank		
3	Form Annex A, B signed by Authorized Signatory		Yes	No
4	Offering specification of items as per tender documents		Yes	No
5	Quoted Currency as per tender documents		Yes	No
6	Accounting unit/Qty as per tender documents		Yes	No
7	Delivery Schedule as per tender documents		Yes	No
8	Certified that there is no Deviation from tender documents conditions/ there is deviation from tender documents condition as per following details.		Yes	No
9	Blacklisting certificate.		Yes	No

Note: Fill and/or mark Yes/No where required.

Signature of Firm Auth Signatory

UNDERTAKING

It is hereby stated and affirmed on oath that M/s_____ (the bidder) is not a member or Administrator of any other company which is participating in the present tender for _____ opened on DD-MM-YYYY, or otherwise no Administrator or employee of the company participating in the bidding process is directly or indirectly in any manner whatsoever involved, associated in any other company / individual business which is bidding in the present bidding process.

It is understood that the above information is correct and at any stage in future if it is found / revealed that the information herein above is not correct, IC shall cancel the bid / contract and the Earnest Money / Security Deposit shall be forfeited by IC. Furthermore, the bidder will be blacklisted for participation against any other tenders.

Tenderer's Signature_____

Name in full _____
Designation _____
Address _____
Phone / Fax # _____
CNIC _____
Seal _____
Date _____

Islamabad Club

Format

Bank Account Details

SR. NO	BUSINESS NAME	ACCOUNT TITLE	ACCOUNT NUMBER	IBAN NUMBER	BANK NAME	WHATSAPP CONTACT NUMBER	OWNER NAME